



ARMY PUBLIC SCHOOL DAMANA

PO Muthi, Jammu -181205

CALL FOR QUOTATIONS

- 1. Army Public School Damana invites quotations from Registered Vendors for Supply and Installation of Additional Safety Measures in the school premises.**
- 2. Vendors must send their representative for on-site assessment of above work. Submit bids by 19 Nov 2025 (1200 hrs) . Quotations should be in separate envelops for Technical and Financial, duly sealed and marked as Tehnical/Financial Quotation for APS Damana.**
- 3. Works to be started immediately after issue of work order. The School/Board of Officers reserves the right to change or vary any part thereof at any stage and also reserves the right to withdraw the project, should it become necessary at any stage/reject the quotations.**

Mob No 6006413231
Website : apsdamana@awesindia.edu.in

Sd/-
Principal

SPECIFICATION FOR CCTV CAMERAS

1	64 Channel Network Video Recorder Box Support ONVIF 384Mbps, Remote User 128, Audio Compression G.711A, G.711, IP Video Input 64 Ch. RCA Audio Input 1 Ch. 4K HDMI Output (3840x2160)/60Hz, VGA Output 1920x1080/60Hz, RCA Audio Output 2 Ch., Two way Audio 1-ch, RCA (Using gthe audio input and output) 16 Ch snapshot, upto 4K resolution, Recording Resolution 32MP CIF, Face Detection, Vehicle Detection, Cross Line Detection, Smart Motion Detection, Intrusion Tetection, Advance H265 Video Compression, SIP (Intrusion Detection, Capacity of Snapshot Record 3 million records for face snapshot, 38 GUI Language, 8 SATA Interface, upto 16 TB for each HDD capacity	1
2	8 TB HDD Surveillance Grade HDD	1
3	2 MP Dome Fixed Eyeball Network Camera High quality image with 2MP, 1/2.8" CMOS sensor, Min Illumination 0.02Lux Day/Night IR & cut filter with auto switch(ICR) Auto shutter, wave length 850nm, Video Stream Dual Streams, Frame Rate Main Stream 080P(1920 1080) Video bit rate 128kbps 6144kbps, Privacy Mask upto 4 area 2MP(1920*1080)@25fps: Advance H265 Comp-ression, 20/30 DNR (Digital Noise Reduction) Audio Compression G711U, G.711A, Audio Bitrate 64 Kbps, ROI (Region of Interest) ONVIF Conformance, Adaptive IR upto 30 Mtr (98ft) IR distance34 2 Axis, Built in Mic, Wide temperature range: -30Degree C- 60Degree CDC 12 V or PoE, IP 67.	52
4	16 Port Unmanaged Ethernet PoE Gigabit Switch, 16x 10/100/1000 MBPS, 1000 Mbps Giga ethernet Ports 1 Combo Ports, Switch Capacity 7.2 Gbps, Forwarding performance 5.36 Mbps, Prior Ports 1 to 8 Standards IEEE802.3, IEEE802.3u, IEEE802.3z IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3az, Power supply AC: 100 to 240V, 50/60Hz, PoE Standard IEEE802.3at, IEEE 802.3af, PoE Mode B(4578)upto 250 m transmission distance on surveillance mode, All metal housing, safe and reliable, Pocket Buffer 4m BIT, MAC 16K, GBPS Uplink. Commercial Grade Max. Power265 W, Max capacity single Port 30W.1 Cooling Fans	2
5	8 Port Unmanaged Poe Gigabit Switch, 8 *10/100/1000 MBPS 1 GBPS Uplink. Commercial Grade	4
6	6 Core OFC Single Mode Armored	500
7	2 Core 1.5.50 mm power cable pure copper	450
8	Cat 6 UTP Cable copper (in meters)	3000
9	Out Door Junction Box Weather Proof	10
10	OFC Media Converter with SEP	2
11	Splicing Jointing Kit with OFC Patch Cord and Joint Enclosure Box	2
12	Accessories Like PVC Pipe, Band, Clamps, Flexible Pipe, connector etc.	